

L e e m i n g L U T P R O

Camera Setup Guide:	DJI Mavic 2 Pro
Colour Space:	Rec709 gamma 2.4
Target Exposure:	ETTR
LUT Version:	Pro 4
Guide Version:	2025.07.17

INTRODUCTION

Thank you for purchasing Leeming LUT Pro™, the most accurate and professional Look Up Tables (LUTs) for your camera.

The LUTs have been carefully developed to get the maximum dynamic range and colour accuracy out of the supported profiles, giving you unparalleled Rec709 precision as well as perfect camera matching with other supported cameras in the Leeming LUT Pro™ range. Use them in conjunction with ETTR shooting principles and you will get the highest possible quality images out of the camera every time.

I am confident you will find these the most accurate LUTs for your camera. Anything less and I wouldn't have put my name on them!

Enjoy :)

Paul Leeming
Director / Writer / Cinematographer / Colorist
Visceral Psyche Films
www.visceralpsyche.com

LICENCE

You are granted a personal licence to use Leeming LUT Pro™ on three devices. For use with more devices, please contact Visceral Psyche Films for bulk discount pricing. You may not upload the LUTs anywhere, share them with other people or incorporate them into other LUTs for derivative use (i.e. making creative LUTs using Leeming LUT Pro™ as the underlying base), whether they be for sale or not. Please respect the work that has gone into the LUTs and support those supporting you.

COMPATIBILITY

Leeming LUT Pro™ is compatible with any software or hardware device that supports a 33x33x33 cube LUT.

REQUIREMENTS

1. DJI Mavic 2 Pro.
2. Spectrally neutral white or grey card, for white balancing the camera.
3. Leeming LUT Pro 4 – DJI Mavic 2 Pro.

NOTE: Items highlighted in yellow have an adverse effect on LUT accuracy if changed away from the recommended values in this guide.

QUICK REFERENCE OF IMPORTANT CAMERA SETTINGS

The settings below are recommended for the LUTs to work properly, in conjunction with an accurate white balance and using the ETTR zebras to show where the highlights of an image are clipping.

If you deviate from these settings, your colorimetry and luma curves won't match precisely to Rec709 and you may get other errors in your footage. You can find the details of how to set these in the next section.

	D-Log M	HLG	Normal
Overexposed	ON	ON	ON
Color	D-Log M	HLG	Normal
Sharpness	+1	+1	+1
Contrast	0	0	0
Saturation	0	0	0

FULL CAMERA SETUP GUIDE

Based on the Mavic 2 Pro, using the DJI Go 4 app interface.

1. Plug your phone or tablet into your remote controller and start the DJI Go 4 app, then press the Connect Aircraft button.
2. Tap on the three dots top right of screen to enter the App Menus.
3. Main Controller Settings – set your max altitude and distance as well the Return to Home Altitude. You can also calibrate your gimbal and compass here, as well as unlocking Geo Zones etc. I recommend setting Signal Lost to Return To Home (make sure your RTH Altitude considers local heights of objects to avoid the drone crashing into them when on autopilot!).
4. Remote Controller Settings – Choose your flight mode etc and Units as desired.
5. Adjust the other settings pages parameters as desired, then exit back to the main camera screen.
6. Tap on the Video/Photo toggle above the Record button and ensure you are in Video mode.
7. Tap on the Settings button under the Record button to enter the camera setup.
8. Tap on the Gear icon – Turn Histogram ON as desired, Overexposed ON, Head LEDs Auto Turn Off ON and the rest as needed. You can also format your SD card here.
9. Tap the Camera icon to the left of the Gear icon and choose your Video Size. Set Video Format as desired.
10. Set Color to the profile you wish to use. I recommend D-Log M as the best option as it is 10bit.
11. Go into the Style sub-menu and set the Custom options: Sharpness +1 (below this causes heavy noise reduction and higher causes edge artifacts), Contrast 0 and Saturation 0. The LUTs are designed to use these values and will look wrong if you alter them away from the recommendation (only sharpness can be altered without affecting the LUTs). Exit the sub-menu.
12. Set White Balance to Custom and adjust to the correct Kelvin value. If you hold a white balance card in front of the drone when switching from Auto to Custom, the

first custom value will be very close to neutral, so this is my recommended method for consistency and avoiding any colour shift during flight. You will need to tweak the white balance in post BEFORE applying the LUT, so I recommend shooting a few seconds of your white balance card before takeoff in the light you expect when flying, for best accuracy in post.

13. Tap on the Iris icon and switch the camera control mode to M (manual adjustment). Here you can set your ISO, Aperture and Shutter speed manually for greater control over your exposure. You can use Auto and then lock the ISO by deselecting the Auto icon next to ISO, to give you more control if you want an in-between option. Use the Overexposure Warning zebras to avoid clipping and ETTR your shots.
14. Exit the Settings back to the main camera screen. At the top right you can adjust your Auto Exposure, AF/MF options and focus point.

You are now ready to use Leeming LUT Pro™ with the maximum picture quality available. Be sure to visit the website to read up on how to use ETTR (Expose To The Right) principles to get the most dynamic range out of your sensor, as well as the associated Leeming LUT Pro™ LUT Installation Manual on how to apply the LUTs to your footage:

www.LeemingLUTPro.com

GUIDE CHANGELOG

2025.07.17 Initial release.